

Specifications

06/21/2015

Project
Bunker Hills Kitchen/Bar Equipment
ALL MISC (B)

From

ITEM 1 - WORK TABLE (1 REQ'D)

Advance Tabco Model SS-486 Dimensions: 35.5(h) x 60(w) x 48(d)

Work Table, 48" wide top, without splash, 72" long, with adjustable undershelf, stainless steel frame & shelf, 14 gauge 304 series stainless steel top, stainless steel bullet feet

- 1 ea Model SCT-60 Pot Rack, table mounted, circular design, 72" long, stainless steel, includes: (18) plated pot hooks & (1) AUR-72 utensil rack
- 4 pk Model TA-89 Pot Hooks, plated, double sided (package of 4)
- 4 ea Model TA-25 X.H.D. Urethane Wheels, for TA25A or TA25 casters (per caster)

ITEM 2 - WORK TABLE (2 REQ'D)

Advance Tabco Model TSS-486 Dimensions: 35.5(h) x 60(w) x 48(d)

Work Table, 48" wide top, without splash, 72" long, with stainless steel legs, side & centered stainless steel crossrails, 14 gauge 304 series stainless steel top, stainless steel bullet feet

- 8 ea Model TA-25C X.H.D. Urethane Wheels, for TA25A or TA25 casters (per caster)

ITEM 5 - FRYER (1 REQ'D)

Pitco Frialator Model SG18S

Solstice Fryer, gas, heavy duty floor model, 70-90 lb. oil capacity, millivolt controls, stainless steel tank, front & sides, 140,000 BTU

- 1 ea 1 year parts and labor warranty from the date of installation up to a maximum of 15 months from the date of manufacture (with appropriate documentation), standard
- 1 ea 10 year parts only stainless steel frypot warranty or 5 year parts only mild steel frypot warranty from the date of manufacture, standard
- 1 ea Natural gas
- 1 ea Model B3901504 Casters, 9" adjustable swivel (set of 4) non-lock rear & lock front casters, solstice supree, SG, SE, VF35 and flat bottom fryers, pasta cookers, rethermalizers, BNB
- 1 ea Model GAS HOSE Gas Connector Hose, 3/4" connection, for castered equipment, 48" long, with quick disconnect couplings, restraining device & thermal shut-off, for single unit 240,000 BTU capacity

ITEM 6 - CHARBROILER (1 REQ'D)

Vulcan Model VACB36 Dimensions: 15.3(h) x 36.13(w) x 31(d)

Achiever Charbroiler, 36" W, countertop, (6) cast iron 17,000 BTU burners with standing pilots and cast iron radiants, heat deflector tray, supercharger burner dividers, high range infinite heat control valves, fully welded chassis, stainless steel front, sides, top trim, backsplash & grease trough, cast iron top grates, 4" adjustable legs, 102,000 BTU, CSA, NSF

- 1 ea 1 year limited parts & labor warranty, standard
- 1 ea Natural gas (add -1 suffix) (specify elevation if over 2,000 ft.)
- 1 ea Model PLTRAIL-ACB36 Plate Rail, 12" deep, stainless steel
- 1 ea Model STAND/C-36 Equipment Stand, universal, 37" W x 24" H, with marine edge, undershelf, stainless steel, 5" casters
- 1 ea Dormont Model 1675KIT48 Blue Hose™ Moveable Gas Connector Kit, 3/4" inside dia., 48" long, covered with stainless steel braid, coated with blue antimicrobial PVC, 1 SnapFast® QD, 1 full port valve, (2) 90° elbows, coiled restraining cable with hardware, 180,000 BTU/hr minimum flow capacity, limited lifetime warranty

ITEM 7 - HEATED CABINET, MOBILE (1 REQ'D)**Alto-Shaam Model 1000-UP Dimensions: 75.81(h) x 22.56(w) x 32.69(d)**

Halo Heat® Heated Holding Cabinet, mobile, double-compartment, on/off simple control with adjustable thermostats, insulated, capacity for (8) 18" x 26" x 1" sheet pans in each compartment, heavy duty 20 gauge stainless steel exterior and interior, 5" heavy duty casters; 2 rigid, 2 swivel with brake, EcoSmart®, cULus, CE, UL ANSI/NSF 4, IP X4

- 1 ea 120v/60/1-ph, 16.0 amp, 1.9kW, 9' cord, NEMA 5-20P
- 1 ea Solid door, hinged on right, standard

ITEM 8 - HEATED BANQUET CART (1 REQ'D)**Alto-Shaam Model 1000-BQ2/128 Dimensions: 67.63(h) x 45.88(w) x 30.81(d)**

Halo Heat® Banquet Cart, 128 plate capacity, ON/OFF power switch, up and down arrow keys, heat indicator light, temperature display key, digital display, electronic control, solid doors, stainless steel construction, (4) 6" heavy duty casters; 2 rigid, 2 swivel with brake, EcoSmart®, cULus, CE, UL ANSI/NSF 4, IP X4

- 1 ea 120v/60/1-ph, 17.5 amp, 2.1kW, 5 ft. cord, NEMA 5-30P
- 1 ea Door hinging: right-hand swing, standard

ITEM 9 - COUNTER (1 REQ'D)**Custom Model COUNTER**

Stainless counter, NSF, 16ga. 9' 6" x 30" deep, dump sink 10" x 14" x 12", 4" deck faucet holes, 4" backsplash, water fill sink to hold 20" x 20" glass rack for filling glasses, open stainless leg base design, splash guard on left side of dump sink, drip tray 36" in front of coffee urn, shop drawing provided and approved prior to fabrication

- 1 ea Fisher Model 1117-WB Banquet Room Glass Filler, deck-mounted, single control valve, vertical riser with flex hose, gooseneck spring, glass filler valve, insulated handle, with wall bracket
- 1 ea Fisher Model 3515 Faucet, deck-mounted, 4" C.C. mixing valve, 12" swing gooseneck spout, with 1/2" inlets
- 1 ea Model WALL SHELF Stainless wall shelf above, counter, 9' 6" x 16", brackets, NSF

ITEM 11 - FIRE PROTECTION WORK (1 REQ'D)**Custom Model FIRE PROTECTION WORK**

Fire protection work, relocate nozzels to support new equipment layout

ITEM 12 - PLUMBING

Gas plumbing, (by others)

ITEM 15 - ROLL-IN REFRIGERATOR (1 REQ'D)**Delfield Model SMRR13-S Dimensions: 89(h) x 98(w) x 34(d)**

Specification Line Series® Refrigerator, Roll-in, three-section, 113.28 cubic feet, self-contained refrigeration 404A, digital thermometer, recessed metal door handle, pressure relief valve, built-in door locks, stainless steel front, aluminum exterior & interior, solid hinged full height door, top mounted compressor, cUL, UL, NSF, 1/2 hp

- 1 ea 115v/60/1, 14.5 amps, NEMA 5-20P, standard
- 1 ea 3 Year parts & labor warranty, standard (USA)

- 1 ea (5) Year compressor warranty standard
- 1 ea Self-contained refrigeration system, standard
- 1 ea Left & center doors hinged on left, right door hinged on right, standard

ITEM 16 - ROLL-IN REFRIGERATOR (1 REQ'D)**Delfield Model SMRR12-S Dimensions: 89(h) x 66(w) x 34(d)**

Specification Line Series® Refrigerator, Roll-in, two-section, 76.34 cubic feet, self-contained refrigeration 404A, digital thermometer, recessed metal door handle, pressure relief valve, built-in door locks, stainless steel front, aluminum exterior & interior, solid hinged full height door, top mounted compressor, cUL, UL, NSF, 1/3 hp

- 1 ea 115v/60/1, 9.5 amps, NEMA 5-15P, standard
- 1 ea 3 Year parts & labor warranty, standard (USA)
- 1 ea (5) Year compressor warranty standard
- 1 ea Self-contained refrigeration system, standard
- 1 ea Self-contained refrigeration system, standard
- 1 ea Left door hinged on left, right door hinged on right, standard

ITEM 17 - EQUIPMENT STAND, REFRIGERATED BASE (1 REQ'D)**Continental Refrigerator Model DL72G Dimensions: 26.38(h) x 72(w) x 34.75(d)**

Refrigerator Griddle Stand, two-section, (4) drawers - two drawers accommodates (1) 12" x 20" x 6" & (1) 6" x 20" x 6", two drawers accommodates (2) 12" x 20" x 6", dial thermometer stainless steel top with drip guard marine edge, stainless steel exterior, interior and back, 4" casters, self-contained refrigeration, 1/4 hp, 10' cord

- 1 ea 115v/60/1, 6.1 amps, NEMA 5-15P, standard
- 1 ea Self-Contained refrigeration, 1/4 hp, standard
- 1 ea Standard warranty (for the United States & Canada Only): 3 year parts and labor; 5 year compressor
- 1 ea Condensing unit on the right, standard
- 1 ea 4" Casters, standard

ITEM 20 - DROP-IN HOT WELL (2 REQ'D)**Wells Model SS-8TDU Dimensions: 10.06(w)**

Food Warmer, top-mount, built-in, electric, for 7-quart round inserts, drain, wet/dry operation, thermostatic control, non-insulated, stainless steel interior, Wellslok, UL, cULus, NSF

- 2 ea Limited 2 year parts & 1 year labor warranty, standard
- 2 ea Model 21562 120v/60/1-ph, 825w, direct
- 1 ea Custom Model MODIFY Modify existing counter, cut 2ea holes for 7qt soup wells, make control apron, support as needed

ITEM 22 - PAN RACK, BUN (4 REQ'D)**New Age Model 1331 Dimensions: 69.75(h) x 20.38(w) x 26(d)**

Bun Pan Rack, mobile, full height, end loading, open sides, accommodates (20) 18" x 26" pans, slides on 3" centers, all welded aluminum construction, (4) 5" platform casters, NSF

- 4 ea Lifetime warranty against rust & corrosion, 5 year construction warranty, std.
- 4 ea 5" platform type casters, std.

ITEM 24 - GLASS DOORS (4 REQ'D)**Glastender Model GLASS DOORS**

Replacement glass doors for back bar solid doors, these will replace solid doors in beer coolers in current bar. These coolers get relocated

ITEM 25 - DROP-IN COLD FOOD PAN (1 REQ'D)**Delfield Model N8118B Dimensions: 21.87(h) x 18(w) x 26(d)**

Drop-In Mechanically Cooled Pan, 1-pan size, 1" dia. drain, insulated pan, stainless steel inner liner & top, galvanized steel outer liner, includes adapter bars, self-contained refrigeration, cUL, UL, NSF-7 (cut-out size 17" x 25"), 1/5 hp

- 1 ea 115v/60/1-ph, 4.0 amps, NEMA 5-15P, standard
- 1 ea Custom Model MODIFY Modify counter, cut hole, make apron, support as needed for drop in refrigerated cold pan, modify flange on drop in to fit table

ITEM 27 - REACH-IN FREEZER (1 REQ'D)**Delfield Model 6125XL-S Dimensions: 79.5(h) x 25.5(w) x 32.6(d)**

Freezer, Reach-in, single-section, 20.0 cubic feet, top mounted self-contained refrigeration 404A, digital thermometer, stainless steel front, aluminum ends, ABS interior, (3) epoxy coated wire shelves, solid hinged full height door, casters, 1/2 hp, cUL, UL, NSF, ENERGY STAR®

- 1 ea 115v/60/1, 9.0 amps, with cord & NEMA 5-15P, standard
- 1 ea (3) Year parts & labor warranty, standard (USA)
- 1 ea 5 Year compressor warranty standard
- 1 ea Door hinged on left

ITEM 28 - COUNTERTOP OVEN (1 REQ'D)**Bakers Pride Model P44-BL Dimensions: 28.5(h) x 26(w) x 28(d)**

HearthBake Series Oven, countertop, electric, pizza/pretzel, brick lined, two compartment, 2-3/4" deck height, (4) removable 20-3/4"W x 20-3/4"D Cordierite hearth decks (2 per deck), 300°F - 650°F thermostat, 15 min. mechanical timer, stainless steel exterior, 7,200w, UL, cUL, CE

- 1 ea One year parts & labor standard
- 1 ea 208v/60/1-ph, 35.4 amps, NEMA 6-50P
- 1 ea 4" Legs, adjustable, standard

ITEM 29 - COUNTERTOP OVEN (1 REQ'D)**Bakers Pride Model P22-BL Dimensions: 17(h) x 26(w) x 28(d)**

HearthBake Series Oven, countertop, electric, pizza/pretzel, brick lined, single compartment, 2-3/4" deck height, two removable 20-3/4"W x 20-3/4"D Cordierite hearth decks, 284°F - 680°F thermostat, 15 min. mechanical timer, stainless steel exterior, 3,600w, UL, cUL, CE

- 1 ea One year parts & labor standard
- 1 ea 208v, 60 hz, 1-ph, 17.3 amps, NEMA 6-20P
- 1 ea 4" Legs, adjustable, standard

ITEM 30 - ANSUL SYSTEM WORK (1 REQ'D)**Custom Model ANSUL SYSTEM**

Ansul system work, adjust nozels, drop to new location

ITEM 31 - ICE CREAM DIPPING CABINET (1 REQ'D)**Silver King Model SKDI/C1 Dimensions: 24.59(h) x 16.59(w) x 16.57(d)**

Freezer, drop-in type, with self-contained refrigeration system, 1 hole, one 3 gallon can capacity, stainless steel interior and top, removable fold back lid, 1/8 HP, ETL Safety, ETL Sanitation

- 1 ea Model DIPPERWELL Wall mount dipperwell to be installed in front of drop in, on stainless worktable
- 1 ea Warranty - 1 year parts & labor, standard
- 1 ea Warranty - additional 4 year compressor, standard

1 ea 115v/60/1ph, 7ft power cord NEMA 5-15P

ITEM 32 - MODIFY (1 REQ'D)**Custom Model MODIFY**

Modify worktable, cut down to approx 9' 3" and finish end, modify leg and undershelf, cut hole for ice cream unit, add bracing, make support for dipperwell, provide drawing prior to modification

ITEM 50 - REFRIGERATED BACKBAR CABINET (2 REQ'D)**Glastender Model BB84 Dimensions: 35(h) x 84(w) x 25.25(d)**

Refrigerated Back Bar Storage Cabinet, three section, 84"W, self-contained refrigeration, galvanized steel sub-top, black vinyl-clad steel exterior front & sides, (3) 180° swing doors with stainless steel handles, (2) adjustable coated shelves & (1) bottom coated rack per door, all stainless steel interior with radius corners, automatic defrost timer & condensate evaporator, 1/2" plastic threshold scuff plate, 1/4 HP, NSF, cETLus

- 2 ea 1 year parts & labor warranty, 5 year compressor warranty
 - 2 ea 120V/60/1-ph 6.5 amps, 6' cord & plug, std.
 - 2 st Model C-6X4-CO Casters (set of six), low profile
 - 2 ea (G) Glass door
 - 2 ea (S) Stainless top
 - 2 ea Model SS-L Left Side, stainless steel
 - 2 ea Model SS-R Right Side, stainless steel
- Only 2ea glass doors, 1 solid door, lowest casters possible

ITEM 51 - MUG CHILLER (1 REQ'D)**Glastender Model MFV24 Dimensions: 36(h) x 24(w) x 25.25(d)**

Mug Froster, front venting, one section, 24"W x 25-1/4"D x 36"H, self-contained refrigeration, holds (108) 10 oz. mugs or (75) 6"H pint glasses, 0°-35°F temperature range, (1) solid door with 180° swing, stainless steel interior with LED lighting, stainless steel sides, includes (2) adjustable shelves & (1) bottom rack, digital thermostat with automatic defrost, automatic condensate evaporator, galvanized sub-top, stainless steel sides, removable refrigeration module, R404A, 6' cord & plug, 1/5 HP, NSF, cETLus, UL, CSA

- 1 ea 1 year parts & labor warranty
- 1 ea 120v/60/1-ph 5.0 amps, 6' cord & plug, std.
- 1 ea (S) Stainless top
- 1 ea (L) Door hinged left
- 1 ea (B) Black vinyl clad door
- 1 ea Model C-4X4-CO Casters, 4" (set of four)

ITEM 52 - SPEED RAIL (2 REQ'D)**Glastender Model CSR-24-SR Dimensions: 8.25(h) x 24(w) x 5(d)**

Single Speedrail, clip-on, 24"W, stainless steel construction, open channel-and-rail design, ABS sound-deadened cover, clear lift-off liquor identification cover, clips on to existing single speed rail, NSF

ITEM 53 - SPEED RAIL (1 REQ'D)**Glastender Model CSR-30-SR Dimensions: 8.25(h) x 30(w) x 5(d)**

Single Speedrail, clip-on, 30"W, stainless steel construction, open channel-and-rail design, ABS sound-deadened cover, clear lift-off liquor identification cover, clips on to existing single speed rail, NSF

ITEM 54 - SPEED RAIL (2 REQ'D)

Glastender Model CSR-36-SR Dimensions: 8.25(h) x 36(w) x 5(d)

Single Speedrail, clip-on, 36"W, stainless steel construction, open channel-and-rail design, ABS sound-deadened cover, clear lift-off liquor identification cover, clips on to existing single speed rail, NSF

ITEM 55 - CASH REGISTER STAND (2 REQ'D)

Glastender Model PCB-24 Dimensions: 24(w) x 24(d)

POS Cabinet, 24"W x 24"D, stainless steel construction, 26"H work surface with cord access hole, louvered locking door with integral handle, splashes on sides & rear, adjustable bullet feet

ITEM 56 - STAINLESS DRIP TRAY WORK (1 REQ'D)

Custom Model STAINLESS DRIP TRAY WORK

Stainless drip tray tower area, provide new stainless drip tray support pan, (drip tray by others), marine edge, flange to cover damaged wood

ITEM 90 - RELOCATE

Relocate equipment: move 2ea back bar coolers #24 to new location in small bar areas, relocate/install bar equipment based on new floor plan, relocate table in banquet kitchen to banquet support kitchen, move stainless work table with sink from banquet kitchen to storage room, move cook line equipment as per plan at both hoods

ITEM 91 - INSTALL (1 REQ'D)

Custom Model INSTALL

Installation to include delivery, set in place, assemble, level, attach, silicone, make ready for final hook up by mechanical trades, remove plastic film, test, start up, review operation with customer and kitchen staff, relocate existing equipment to new locations (see item #90, work will be done during business hours and possible after hours based on construction schedule of GC in different areas. Multiple trips may be needed as this is a renovation of the business and will remain open.

ITEM 92 - FREIGHT (1 REQ'D)

Custom Model FREIGHT

Freight from factory to job site or warehouse
